

NDL INDUSTRIES INC.

Contactors



Part No.	Poles	Full Load Amps	Coil Voltage	Line Voltage	Locked Rotor Amps	Resistive Amps Rating	Maximum Horsepower			Unit Weight (approx.)
							Voltage	Single Phase	Three Phase	
CN-PBC201	1	20	24V	240/277	120	30	120	1	0.5 lb. 0.23 kg	
			120V	480	100	30	240	2		
			208/240V	600	80	30				
CN-PBC251	1	25	24V	240/277	150	30	120	1	0.5 lb. 0.23 kg	
			120V	480	125	30	240	2		
			208/240V	600	100	30				
CN-PBC301	1	30	24V	240/277	180	40	120	1	0.5 lb. 0.23 kg	
			120V	480	150	40	240	2		
			208/240V	600	120	40				
CN-PBC401	1	40	24V	240/277	240	50	120	2	0.5 lb. 0.23 kg	
			120V	480	200	50	240	3		
			208/240V	600	160	50				
CN-PBC202	2	20	24V	240/277	120	30	120	2	0.6 lb. 0.27 kg	
			120V	480	100	30	240	3		
			208/240V	600	80	30				
CN-PBC252	2	25	24V	240/277	150	35	120	2	0.6 lb. 0.27 kg	
			120V	480	125	35	240	3		
			208/240V	600	100	35				
CN-PBC302	2	30	24V	240/277	180	40	120	2	0.6 lb. 0.27 kg	
			120V	480	150	40	240	3		
			208/240V	600	120	40				
CN-PBC402	2	40	24V	240/277	240	50	120	2	0.6 lb. 0.27 kg	
			120V	480	200	50	240	3		
			208/240V	600	160	50				
CN-PBC203	3	20	24V	240/277	120	30	110/120	1.5	1 lb. 0.45 kg	
			120V	480	100	30	200/240	3		7.5
			208/240V	600	80	30	480/600	7.5		
CN-PBC253	3	25	24V	240/277	150	35	110/120	2	1 lb. 0.45 kg	
			120V	480	125	35	200/208	7.5		
			208/240V	600	100	35	240/277	5		10
CN-PBC303	3	30	24V	240/277	180	40	200/208	10	1 lb. 0.45 kg	
			120V	480	150	40	240/277	5		10
			208/240V	600	120	40	480	15		20
CN-PBC403	3	40	24V	240/277	240	50	200/208	10	1 lb. 0.45 kg	
			120V	480	200	50	240/277	7.5		10
			208/240V	600	160	50	480	20		25
CN-PBC503	3	50	24V	240/277	300	65	110/120	3	2 lb. 0.91 kg	
			120V	480	250	65	200/208	7.5		15
			208/240V	600	200	65	240/277	10		15
CN-PBC603	3	60	24V	240/277	360	75	200/208	7.5	2 lb. 0.91 kg	
			120V	480	300	75	240/277	10		25
			208/240V	600	240	75	480	7.5		30
CN-PBC753	3	75	24V	240/277	450	93	110/120	5	4 lb. 1.81 kg	
			120V	480	375	93	200/208	10		20
			208/240V	600	300	93	240/277	15		25
CN-PBC903	3	90	24V	240/277	540	120	200/208	15	4 lb. 1.81 kg	
			120V	480	450	120	240/277	20		30
			208/240V	600	360	120	480	50		50